

ALERT DISASTER CONTROL

Global Emergency Response and Integrated Risk Management Solutions



The **ALERT** range of threaded couplings are selected from international OEM's that produce high quality extruded 6061-T6 lightweight aluminium alloy, adapters, hard anodised threaded fittings ranging from 3/4" to 8.0". The finished products are laser engraved with a clear understanding of the thread type and size produced. Swivel sizes ranging from 1.0" to 8.0" are attached using ball bearings. Coupling type and size to customer specification.

Thread (FxF) Swivel Adapters

Double Female Swivel Adapters supplied with Rocker Lug. Made for adapting from male to female.



Thread (MxM) Rigid Adapters

Double Threaded Male Adapters supplied with Rocker Lug. Made for adapting from female to male.



Thread (FxM) Rigid Adapters

Female Rigid Thread to Male Thread with Rocker Lug.



Thread (FxF) Rigid x Swivel Adapters

Female Swivel Threaded Rocker Lug to Female Rigid Rocker Lug. Made for adapting male to female.



Hose Couplings & LDH Systems

www.alertdisastercontrol.com

ALERT (Asia) • ALERT (Canada) • ALERT (Middle East) • ALERT (Oceania) • ALERT (USA)

ALERT maintain an Integrated QHSE Management System to ISO 9001, ISO 14001 and OHSAS 18001 Standards as Certified by Det Norske Veritas

ALERT DISASTER CONTROL

Global Emergency Response and Integrated Risk Management Solutions



Thread (FxM) Swivel Adapters

Female Swivel Threaded Long Handle or Rocker Lug to Male Thread.



Thread (FxM) Rigid Adapters

Female Rigid Threaded Long Handle to Male Thread.



Thread (FxF) Swivel Adapters

Double Female Swivel Adapters supplied with Long Handle. Made for adapting male hydrant or suction hose thread to female hose thread.



CAP Adapters

One piece Male Threaded Plug, with or without 12" coated aircraft cable.



Hose Couplings & LDH Systems

www.alertdisastercontrol.com

ALERT (Asia) • ALERT (Canada) • ALERT (Middle East) • ALERT (Oceania) • ALERT (USA)

ALERT maintain an Integrated QHSE Management System to ISO 9001, ISO 14001 and OHSAS 18001 Standards as Certified by Det Norske Veritas

ALERT DISASTER CONTROL

Global Emergency Response and Integrated Risk Management Solutions



Hose Couplings & LDH Systems

Blank CAP

Two part Female Threaded Cap, with or without 12" coated aircraft cable. Available drilled and tapped 1/4" NPT. Also available with petcock at an additional charge. Supplied with Rocker Lug as standard. Long Handle available upon request.



Storz Blank Caps with Chain

Storz blank caps range in size from 1.0" through 8.0". Made from Forged Aluminum 6061-T6 material. Heads are supplied hard coat anodized for added corrosion resistance. Caps are provided complete with fastening chain.



Storz Adapters

Storz adapter heads range in size from 1.0" to 8.0". Made from Forged Aluminum 6061-T6 material. Heads are supplied hard coat anodized for added corrosion resistance. All sizes between 4.0" through 8.0" are supplied with Metal Locking Device meeting NFPA 1963 standards. Thread size and type to be specified by customer.



Expansion Ring Couplings

Expansion ring couplings are made from 6061-T6 aluminum alloy. All couplings are supplied hard coat anodized for added corrosion resistance and durability. Swivel sizes ranging from 1-1/2" through 2-1/2" couplings attach via a piston ring. While swivel sizes ranging from 3.0" through 8.0" are attached using roller bearings.



www.alertdisastercontrol.com

ALERT (Asia) • ALERT (Canada) • ALERT (Middle East) • ALERT (Oceania) • ALERT (USA)

ALERT maintain an Integrated QHSE Management System to ISO 9001, ISO 14001 and OHSAS 18001 Standards as Certified by Det Norske Veritas

ALERT DISASTER CONTROL

Global Emergency Response and Integrated Risk Management Solutions



Hose Couplings & LDH Systems

Storz 3-Part Bindings

Storz large diameter delivery coupling comes complete with locking coupling head, 3-part collar and shank. This coupling is designed for use with 4.0" through 8.0" large diameter supply hose.



Coupling Gaskets

A wide range of gaskets for LDH appliances are available ranging from 1.0" to 8.0".



Storz Suction Hose Couplings

Storz suction couplings are supplied for use with hard rubber suction hose and available in sizes from 1.0" through 8.0". The coupling is attached to the hose using wire clamps.



Hose Spanners and Brackets

Combination hose and coupling spanners are available for virtually all coupling and adapter styles from 1.0" through 8.0". Adjustable Hydrant Wrenches and Combination Tools are available in various configurations to meet coupling combinations.



Coupling Mounting Bracket

Aluminum mounting plates are hard anodized and are available in two sizes. One plate is used for 1.5" and 2.5" storz adapters. The other plates are available for 4.0", 5.0", 6.0" and 8.0" Storz adapters. Coupling mounting brackets are available in a broad range of coupling types and sizes.



www.alertdisastercontrol.com

ALERT (Asia) • ALERT (Canada) • ALERT (Middle East) • ALERT (Oceania) • ALERT (USA)

ALERT maintain an Integrated QHSE Management System to ISO 9001, ISO 14001 and OHSAS 18001 Standards as Certified by Det Norske Veritas