



STORM ALERT™ RF 3% SYNTHETIC FOAM CONCENTRATE

Description

STORM ALERT™ RF3% is a flammable liquid fire fighting foam achieving International accreditation with excellent performance while minimizing environmental impact. STORM ALERT™ RF3% is a versatile foam concentrate which has been developed for use in a wide range of fire protection applications specific to Class B flammable and combustible liquid fuels and Class A wetting agent applications.

STORM ALERT™ RF3% is a multipurpose synthetic fire fighting foam designed for a broad range of applications through conventional fire protection equipment and systems using fresh, sea and or brackish waters. STORM ALERT™ RF3% delivers rapid-fire extinguishment of hydrocarbon fuels and partially water-soluble flammable liquids such as blended gasohols. STORM ALERT™ RF3% represents an inherent resilience to burn back while providing sustainable longevity of flammable, toxic or noxious vapour suppression and homogenous stability with superior drain time.

Application

STORM ALERT™ RF3% is recommended for use in fixed systems and with a wide variety of conventional and specialized fire fighting and vapour suppression foam proportioning and delivery devices.

Examples of delivery equipment are listed, yet not limited to, the following:

Delivery Equipment:

- Non-aspirating and aspirating foam nozzles and branches
- Self-educing foam nozzles
- High volume delivery monitors
- Dual agent applicators
- Sprinkler systems.

Fixed Systems:

- Aircraft hanger floor pup-up and overhead foam sprinkler systems
- Industrial and marine bladder tank systems
- Atmospheric in-line balanced pressure
- Foam chambers/foam pourers
- Semi-subsurface devices
- Medium expansion foam
- Fixed foam making deliveries generators
- This includes all NFPA 11 Type I, II, and III application devices.

Performance

Fire Performance

STORM ALERT™ RF3% has been tested to international industry standards representing optimum fire fighting performance for volatile flammable and combustible liquids. STORM ALERT™ RF3% is the World's first AFFF/FFFP alternative Class B flammable liquid fire fighting foam to receive Aviation's highest performance certification of (ICAO Level-B) issued by DNV to the International Civil Aviation Organization Standards.



Foam Proportioning

STORM ALERT™ RF3% foam concentrate can be proportioned at the proper foam solution percentages using common foam proportioning device such as:

- Inline venturi eductors
- Balanced pressure proportioning
- Round the pump
- Through the pump
- Bladder tank ratio controllers
- Self educating delivery devices
- Pre mix solution

Storage

STORM ALERT™ RF3% shelf lifetime is expected to be 10 years (minimum) when stored in suitable containers, Storage of premix solution is not recommended for periods in excess of 12 months. Annual inspection of fire protection systems and foam concentrate. as prescribed in NFPA-11, NFPA-25, and AS1940, are recommended as good practice. No foam concentrate should be mixed in storage with other agents.

GLOBAL EMERGENCY CONTACT NUMBER
+(65) 6545 5088 (24Hrs)

ALERT DISASTER CONTROL (ASIA) PTE. LTD.

Box 5008, Blk 203, Unit #01-00 Loyang Offshore Supply Base, Loyang Crescent, Singapore 508988
T: [65] 6545 5088 [24 Hrs] • F: [65] 6545 3033 • E: stormalertsales@alert.com.sg • W: alertdisastercontrol.com
ALERT (Asia) • ALERT (Canada) • ALERT (Middle East) • ALERT (USA) • ALERT (Russia)



Compatibility

Dry chemical compatible when used with listed water-insoluble dry chemical powders.

Generally when applied to a fire the product can be mixed with other similar foam types. However the foam concentrate should not be mixed with other brands of concentrate.

Inspection

STORM ALERT™ RF3% foam concentrate or premix solution should be inspected per National Fire Protection (NFPA) Standards 11 and 25. A sample of the foam concentrate should be sent to the manufacturer for quality conditioning testing in accordance to NFPA11.

Environmental Information

STORM ALERT™ RF3% concentrate has undergone strenuous testing to assess the impact of the fire fighting foams on the environment and living organisms.

Data indicates that:

- STORM ALERT™ RF3% is low in toxicity to tested aquatic organisms, readily biodegradable and is not identified with any persistent or bio-accumulative ingredients. (Toxicity information is available from Product Environmental Data Sheets, Material Safety Data Sheets and Toxicity Summary Sheets for individual products).
- Aquatic life is not adversely affected when STORM ALERT™ Series products are used and disposed of properly.
- STORM ALERT™ Series products can be successfully treated in biological wastewater treatment systems.

Approval & Listings

ALERT manufactured products are thoroughly inspected and undergo rigorous quality control tests. These evaluations analyze the foam's physical parameters as well as the finished product's fire performance. A Certificate of Analysis (COA) is issued with every batch.

STORM ALERT™ RF3% has EN 1568 part 3 approval and meet ICAO-B regulations.

Ordering Information

STORM ALERT™ RF3% foam concentrate is available in pails, drums, totes and bulk quantities.

PROPERTIES	
Visual:	Brown non-newtonian liquid
Specific gravity (25°C):	1,06 kg/l
pH (25°C):	8,0
Viscosity:	Pseudoplastic liquid (5,100 cps)
Frost resistance:	Product has a freezing stretch starting at a -2° C
Freezing Point:	23°F (-5°C)
Minimum use temp:	2° C
Maximum storage temp:	< 50° C
Sediments:	none

<i>Foam expansion depending on water pressure and type of equipment:</i>	
<i>very low expansion:</i>	between 1.5 and 4
<i>low expansion:</i>	between 8 and 20
<i>medium expansion:</i>	between 20 and 50
<i>high expansion:</i>	up to 500
<i>25% drainage time:</i>	> 5 min till 15 min
<i>(depending on water pressure and type of equipment used)</i>	
<i>Product guarantee:</i>	10 years when stored in original package
<i>Salt, fresh and brackish water can be used.</i>	

DESCRIPTION	SHIPPING WEIGHT	CUBE
STORM ALERT™ RF3%, 5 gallon (20 litre) pail	45 lb (21 kg)	1.25 ft ³ (0.04 m ³)
STORM ALERT™ RF3%, 55 gallon (200 litre) drum	495 lb (224 kg)	11.83 ft ³ (0.33 m ³)
STORM ALERT™ RF3%, 265 gallon (1000 litre) tote	2465 lb (1118 kg)	50.05 ft ³ (1.42 m ³)
STORM ALERT™ RF3%, bulk	Call Customer Services	

ALERT DISASTER CONTROL (ASIA) PTE. LTD.

Box 5008, Blk 203, Unit #01-00 Loyang Offshore Supply Base, Loyang Crescent, Singapore 508988
 T: [65] 6545 5088 [24 Hrs] • F: [65] 6545 3033 • E: stormalertsales@alert.com.sg • W: alertdisastercontrol.com
 ALERT (Asia) • ALERT (Canada) • ALERT (Middle East) • ALERT (USA) • ALERT (Russia)